

1. Chemical Product and Company Identification

Polytek Development Corp., 55 Hilton St., Easton, PA 18042, 610/559-8620

Product Name: **PlatSil[®] Part A**
(71-10A, 71-11A, 71-20A, 71-30A, 71-35A, 71-40A)

Chemical Family: Organofunctional-siloxanes

2. Hazardous Constituents

Hazardous Ingredient/CAS #	Exposure Limits
Organofunctional-siloxanes	None established
Additional information on ingredients is withheld as a trade secret per 29 CFR 1910.1200(i).	

3. Health Hazards

PRIMARY ROUTE(S) OF ENTRY: Skin or eye contact
EYE: May cause slight eye irritation. Corneal injury is unlikely.
SKIN: May cause slight skin irritation
INGESTION: Essentially non-toxic by ingestion -- may cause gastrointestinal discomfort.
INHALATION: At room temperature, no harmful effects expected. Vapors from heated material may cause respiratory irritation.
CARCINOGENICITY: Not designated as a carcinogen by NTP, IARC, or OSHA.

4. First Aid Measures

EYE CONTACT: Flush with plenty of water. Seek medical attention if irritation persists.
SKIN CONTACT: Wipe off and wash with soap and plenty of warm water.
INHALATION: Remove to fresh air. Seek medical attention if symptoms persist.
INGESTION: Seek medical attention. Do not induce vomiting unless so directed by a medical professional.

5. Fire Fighting Measures

FLASH POINT: >200°F (estimated)
EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, foams, or water spray.
HAZARDOUS COMBUSTION PRODUCTS: May include carbon and silicone oxides and potentially irritating compounds such as formaldehyde.
OTHER INFORMATION: Firefighters wear SCBA. Application of water stream to hot product may cause frothing and increase fire intensity. This material may produce a floating fire hazard.

6. Accidental Release Measures

Clear non-emergency personnel from the area. Remove sources of ignition. Contain spill to minimize environmental contamination. Absorb spilled material with an absorbent such as sawdust, vermiculite, dirt, sand, clay, or cob grit. Collect and containerize material.

7. Handling and Storage

HANDLING: Use in adequately ventilated area. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke in work area. Wash hands after handling. See also Section 8 of MSDS.
STORAGE: Store in a cool, dry area. Store in original, closed container.

8. Exposure Controls/Personal Protection

ENGINEERING CONTROLS: Provide general and/or local exhaust. At room temperature, special exhaust is not needed.
PERSONAL PROTECTIVE EQUIPMENT: Eye protection (e.g., chemical splash goggles), and rubber gloves are recommended.
RESPIRATORY PROTECTION: Under normal conditions, respiratory protection is not required. In emergencies, use SCBA.

9. Physical Characteristics

APPEARANCE: 71-10A and 71-40A are clear and colorless; 71-11A, 71-20A and 71-35A are blue; and 71-30A is green
ODOR: Mild
pH: Not determined
BOILING POINT: >200°F
VAPOR PRESSURE: <1 mm Hg @ 25°C
SOLUBILITY IN WATER: Insoluble
SPECIFIC GRAVITY: 1.0 @ 20°C, except 71-20A is approx. 1.1

10. Stability and Reactivity

CONDITIONS TO AVOID: Normally stable, but avoid temperatures in excess of 120°F.
INCOMPATIBILITY WITH OTHER MATERIALS: Avoid contact with acids, alkalis, alcohols, and strong oxidizers. Reaction with powdered metals and metallic oxides may react to form flammable hydrogen gas.
HAZARDOUS DECOMPOSITION PRODUCTS: Depends on temperature, air supply and presence of other materials; likely to form oxides of carbon and silicone, and possibly hydrogen gas and formaldehyde.

11. Regulatory and Other Information

COMMUNITY RIGHT-TO-KNOW: This product does not contain any compounds above the de minimis reporting levels subject to SARA Section 313 reporting requirements.
DISPOSAL: Upon disposal, this product is not a listed or characteristic RCRA hazardous waste as defined in 40 CFR 261. Dispose of in accordance with state and local regulations.
TRANSPORT: Not a hazardous material for shipping purposes based on *United Nations Recommendations for the Transport of Dangerous Goods* and 49 CFR Part 171.
HMIS RATING: Health-1; Flammability-1; Physical Hazard-0
NFPA RATING: Health-1; Flammability-1; Reactivity-0
EMERGENCY SHIPPING INFORMATION: Call CHEMTREC, 800/424-9300.
MSDS REVISION INDICATOR: Minor format changes.
DISCLAIMER: The information contained herein is considered accurate; however, Polytek makes no warranty regarding the accuracy of the information. The user must determine the suitability of the product for the intended use and accepts all risk and liability associated with that use.