

1. Chemical Product and Company Identification

Polytek Development Corp., 55 Hilton St., Easton, PA 18042, 610/559-8620
Product Name: **TINSIL® PART B (70-11B, 70-20B, 70-25B, 70-30B, 70-39B, 70-60B)**
Chemical Family: Silicone

2. Hazardous Constituents

Hazardous Ingredient/CAS #	Exposure Limits
Organofunctional-siloxanes	None established
Silica	Not applicable (not present as a dust)
Additional information on ingredients is withheld as a trade secret per 29 CFR 1910.1200(i).	

3. Health Hazards

PRIMARY ROUTE(S) OF ENTRY: Skin or eye contact
EYE: May cause eye irritation.
SKIN: May cause irritation or redness.
INGESTION: May cause gastrointestinal discomfort.
INHALATION: At room temperature, no harmful effects expected. Vapors from heated material may cause respiratory irritation.
CARCINOGENICITY: Not designated as a carcinogen by NTP, IARC, or OSHA.
CHRONIC EFFECTS: No information found concerning adverse chronic health effects.

4. First Aid Measures

EYE CONTACT: Flush with plenty of water. Seek medical attention if irritation persists.
SKIN CONTACT: Wipe off and wash with soap and plenty of warm water.
INHALATION: Remove to fresh air. Seek medical attention if symptoms develop.
INGESTION: Seek medical attention. Do not induce vomiting unless so directed by a medical professional.

5. Fire Fighting Measures

FLASHPOINT: >350°F (estimated)
EXTINGUISHING MEDIA: Water spray, carbon dioxide, dry chemical or foams
HAZARDOUS COMBUSTION PRODUCTS: May include carbon and silicone oxides and potentially irritating compounds such as formaldehyde.
OTHER INFORMATION: Firefighters wear self-contained breathing apparatus (SCBA).
Application of water stream to hot product may cause frothing and increase fire intensity. This material may produce a floating fire hazard. If possible, keep fire-exposed containers cool with water spray to prevent rupture.

6. Accidental Release Measures

Clear non-emergency personnel from the area. Remove sources of ignition. Contain spill to minimize environmental contamination. Absorb spilled material with an absorbent such as sawdust, vermiculite, dirt, sand, clay, or cob grit. Collect and containerize material.

7. Handling and Storage

HANDLING: Use in adequately ventilated area. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke in work area. Wash hands after handling. See also Section 8 of MSDS.
STORAGE: Store in a cool, dry area in original container. Keep tightly closed when not in use.

8. Exposure Controls/Personal Protection

ENGINEERING CONTROLS: Provide general and/or local exhaust. At room temperature, no special exhaust is needed.
PERSONAL PROTECTIVE EQUIPMENT: Eye protection (e.g., chemical splash goggles), and rubber gloves are recommended.
RESPIRATORY PROTECTION: Under normal conditions, respiratory protection is not required. In the absence of good ventilation, may use respirator equipped with organic vapor cartridges: in emergency situations, use SCBA.

9. Physical Characteristics

APPEARANCE: White to off-white opaque liquid, VISCOSITY: 20,000-70,000 cP
except 70-30B is beige and 70-60B is red VAPOR PRESSURE: Not determined
ODOR: Mild SOLUBILITY IN WATER: Insoluble
pH: Not applicable SPECIFIC GRAVITY: 1.1-1.5 @ 20°C
BOILING POINT: Not determined

10. Stability and Reactivity

CONDITIONS TO AVOID: Normally stable, but avoid prolonged storage at elevated temperatures to assure product integrity.
INCOMPATIBILITY WITH OTHER MATERIALS: None known.
HAZARDOUS DECOMPOSITION PRODUCTS: Depends on temperature, air supply and presence of other materials; likely to form oxides of carbon and silicone, possibly formaldehyde.

11. Regulatory and Other Information

COMMUNITY RIGHT-TO-KNOW: This product does not contain any compounds above the *de minimis* reporting levels subject to SARA Section 313 reporting requirements.
DISPOSAL: Upon disposal, this product is not a listed or characteristic RCRA hazardous waste as defined in 40 CFR 261. Dispose of in accordance with state and local regulations.
TRANSPORT: Not a hazardous material for shipping purposes based on *United Nations Recommendations for the Transport of Dangerous Goods* and 49 CFR Part 171.
HMIS: Health=1; Flammability=0; Reactivity=0; PPE=C
EMERGENCY SHIPPING INFORMATION: Call CHEMTREC, 800/424-9300.
MSDS REVISION INDICATOR: Changed 70-10 to 70-11 and deleted 70-26. Also, made several minor revisions.
DISCLAIMER: The information contained herein is considered accurate; however, Polytek makes no warranty regarding the accuracy of the information. The user must determine the suitability of the product for the intended use and accepts all risk and liability associated with that use.