

1. Chemical Product and Company Identification

Polytek Development Corp., 55 Hilton St., Easton, PA 18042, 610/559-8620
Product Name: **TINSIL® FASTCAT**
Chemical Family:Silicone

2. Hazardous Constituents

Hazardous Ingredient/CAS #	Exposure Limits
Organotin compound	ACGIH TLV 0.1 mg/m ³ TWA (skin), 0.2 mg/m ³ STEL OSHA PEL 0.1 mg/m ³
Polyalkylorthosilicate, 78-10-4	ACGIH TLV 85 mg/m ³ or 10 ppm TWA OSHA PEL 850 mg/m ³ or 100 ppm TWA

3. Health Hazards

PRIMARY ROUTE(S) OF ENTRY: Inhalation, skin or eye contact, ingestion
EYE: May cause serious eye irritation and pain.
SKIN: May cause irritation and pain.
INGESTION: May cause malaise and irritation to the mouth, throat, esophagus and stomach.
INHALATION: May cause respiratory irritation, dizziness, headache, or confusion. But, at room temperature, vapors are expected to be minimal.
CARCINOGENICITY: Not designated as a carcinogen by NTP, IARC, or OSHA.
CHRONIC EFFECTS: Prolonged/repeated exposure may cause sore throat; adverse eye, skin, and respiratory effects; possible liver and kidney damage; and central nervous system disorders.
TARGET ORGANS: Eye, skin, liver, kidney, and central nervous system

4. First Aid Measures

EYE CONTACT: Flush with plenty of water for at least 15 minutes while holding eyelids apart. Remove contact lenses. Seek medical attention if irritation persists.
SKIN CONTACT: Remove contaminated clothing. Wash with soap and warm water for 15 min.
INHALATION: Remove to fresh air. Seek medical attention if breathing is difficult.
INGESTION: Seek medical attention. Do not induce vomiting unless so directed by a medical professional.

5. Fire Fighting Measures

FLASHPOINT: 112°F (Pensky-Martin Closed Cup)
EXTINGUISHING MEDIA: Water spray, carbon dioxide, dry chemical or foams
HAZARDOUS COMBUSTION PRODUCTS: May include carbon and silicone oxides and potentially irritating compounds such as formaldehyde.
OTHER INFORMATION: Firefighters wear self-contained breathing apparatus (SCBA).
Application of water stream to hot product may cause frothing and increase fire intensity. This material may produce a floating fire hazard. If possible, keep fire-exposed containers cool with water spray to prevent rupture.

6. Accidental Release Measures

Clear non-emergency personnel from the area. Remove sources of ignition. Contain spill to minimize environmental contamination. Absorb spilled material with an absorbent such as sawdust,

vermiculite, dirt, sand, clay, or cob grit. Collect and containerize material. Cleanup personnel wear protective equipment (see Section 8).

7. Handling and Storage

HANDLING: Use in adequately ventilated area. Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke in work area. Wash hands after handling. See also Section 8 of MSDS.
STORAGE: Store in a cool, dry area. Store in original, closed container.

8. Exposure Controls/Personal Protection

ENGINEERING CONTROLS: Provide general and/or local exhaust. At room temperature, no special exhaust is needed.
PERSONAL PROTECTIVE EQUIPMENT: Eye protection (e.g., chemical splash goggles), and butyl rubber gloves are recommended.
RESPIRATORY PROTECTION: Under normal conditions, respiratory protection is not required. In the absence of good ventilation, may use respirator equipped with organic vapor cartridges: in emergency situations, use SCBA.

9. Physical Characteristics

APPEARANCE: Clear colorless liquid
ODOR: Mild odor
pH: Not applicable
BOILING POINT: Not determined
VISCOSITY: 50-100 cP
VAPOR PRESSURE: <1 mm Hg @ 25°C
SOLUBILITY IN WATER: Insoluble
SPECIFIC GRAVITY: ~1.0 @ 20°C

10. Stability and Reactivity

CONDITIONS TO AVOID: Normally stable, but avoid prolonged storage at high temperatures.
INCOMPATIBILITY WITH OTHER MATERIALS: Avoid contact with minerals acids (e.g., sulfuric and phosphoric), oxidizers (e.g., perchlorates, nitrates).
HAZARDOUS DECOMPOSITION PRODUCTS: Depends on temperature, air supply and presence of other materials; likely to form oxides of carbon and silicone, possibly formaldehyde.

11. Regulatory and Other Information

COMMUNITY RIGHT-TO-KNOW: This product does not contain any compounds above the *de minimis* reporting levels subject to SARA Section 313 reporting requirements.
DISPOSAL: Upon disposal, this product is not a listed RCRA hazardous waste but may be RCRA ignitable (D001) as defined in 40 CFR 261. 70-39A properly cured with 70-39B is not a hazardous waste. Dispose of in accordance with regulations.
TRANSPORT: By ground, not regulated as a hazardous material (Combustible liquid, n.o.s.). By air: Flammable liquid, n.o.s. (polyalkylorthosilicate), 3, UN 1993, III. By boat, contains Marine Pollutant (organotin compound).
EMERGENCY SHIPPING INFORMATION: Call CHEMTREC, 800/424-9300.
HMIS: Health=2; Flammability=2; Reactivity=0; PPE=C
MSDS REVISION INDICATOR: Minor format changes.
DISCLAIMER: The information contained herein is considered accurate; however, Polytek makes no warranty regarding the accuracy of the information. The user must determine the suitability of the product for the intended use and accepts all risk and liability associated with that use.